

Moonlight™

Product Code	Construction	Material	Weight	Thickness	Max Width
iTex	Warp-knit	100% Coated PES/FR	8.99 oz/sq.yd	0.64 mm	126 in.
iTex-RY	Warp-knit	100% Recycled PES			
iTex-T	Warp-knit	100% Uncoated PES			

Description

Knitted Backlit Crease Free Fabric

Features

Ideal For Backlit, Crease free, Excellent Durability

Applications

Backlit | POP UP | SEG | Trade Show

Ink Compatibility

Dye Sub Transfer | Dye Sub Direct | UV | Latex

Print Side

Sublimation | Both

Shrink (l):	1.53%
Shrink (w):	0.40%
Stretch (l):	1.87%
Stretch (w):	1.47%
Stretch at Burst (l):	77.00%
Stretch at Burst (w):	70.00%
Burst Strength (l):	70lbs/in.
Burst Strength (w):	411 lbs/in.
Tensile Strength (l):	3 lbs/in.
Tensile Strength (w):	9 lbs/in.
Burst Strength:	217 lbs
Yellowing:	0.87 dE
Max Roll Length:	100m
Available Recycled:	Yes
Available Anti-microbial:	Yes



All fabrics are NFPA-701 flame Retardant Certified/B1 M1 Certifications Available on Request.
Recommended transfer settings for sublimation are 374°F-190°C°F for 40 seconds at 40psi.